

# MULTISWITCH [SMWx-x]

Multiswitch, Satellite




## Features

- 950–2150 MHz bandwidth
- Cascadable multiswitch or Terminal multiswitch
- Input options: 2, 3, or 4
- 4, 6, or 8 receivers
- Built in amplification circuit to compensate cable loss
- Suitable for residential multiple LNBS reception
- Raised housing. Casing made of tinplated sheet metal



## Ordering Information



	<b>Insertion Loss</b>	<b>SMW2-x</b>	<b>SMW3-x</b>	<b>SMW4-x</b>
Frequency	<b>5–950 MHz</b>	x dB	1.0 dB	x dB
	<b>951–2150 MHz</b>	2.5 dB	2.5 dB	2.5 dB
	<b>Input/Output Return Loss</b>	<b>SMW2-x</b>	<b>SMW3-x</b>	<b>SMW4-x</b>
Frequency	<b>5–950 MHz</b>	x dB	12 dB	x dB
	<b>951–2150 MHz</b>	12 dB	12 dB	12 dB
	<b>Isolation</b>	<b>SMW2-x</b>	<b>SMW3-x</b>	<b>SMW4-x</b>
Frequency	<b>5–950 MHz</b>	x dB	18 dB	x dB
	<b>951–2150 MHz</b>	30 dB	20 dB	20 dB

\*Specifications are subject to change without notice. v1.00