



2.4 GHz

ASU-24005G

the best solution for your wifi coverage!

802.11 **b** **g** **WiFi**

Features:

- Easy Installation
- Configuration options : Access Point / Client / Repeater / Bridge
- 2.4 GHz operation frequency
- Low cost solution
- IEEE 802.11 b/g compliant
- Enclosed 12 dBi flat panel antenna
- 64 bit / 128 bit WEP encryption
- Coverage range: 3-5 km

Ordering Information:

	Std Qty	Physical Dimension (LxWxH)	Weight	Accessories Include:
ASU-24005G	1 pc	7x4.5x2.5 inches	1 lb	POE / Bracket / Power Adapter / CAT5E cable



ASU-24005G Features:

Standard Compliance	IEEE 802.11b/g IEEE 802.3 IEEE 802.3u
Radio Frequency type	DSSS/OFDM
Modulation	IEEE 802.11b : CCK, DQPSK, DBPSK IEEE 802.11g : OFDM
Frequency Band	2.412-2.462 GHz (11 channels)
Operating Channel	
Transmission	
Output Power	IEEE 802.11b/g : 20 dBm
Transmission Rate	IEEE 802.11b : 1/2/5.5/11 Mbps IEEE 802.11g : 6/9/12/18/24/36/48/54 Mbps Super G: up to 108 Mbps
Physical Interfaces	Auto MDI / MDI-X 10/100 Base-TX: RJ-45
Sensitivity	'-86 dBm @ 11 Mbps, PER < 8% '-64 dBm @ 54 Mbps, PER <10%
Antenna Type	Integrated 12 dBi flat panel antenna
Security Systems	64 / 128 / 152 bit WEP encryption Wi-Fi protected access (WPA)
Wireless Setting	Access Point Client Repeater Bridge Point to Point (PtP) Point to Multipoint (PtMP)
Software / Firmware	Site Survey DHCP Client Wireless access control by MAC address WPA Support (WPA personal and enterprise) Web-based configuration Firmware upgrade and configuration backup Reset to default by WebUI
Operating Temperature	-10C ~ +70C
PoE	12 VDC ; 2A
Adapter	100-240 VAC
Regulatory Approval	FCC Part 15B ; CE
Network Management	Windows 2000/XP
System OS Support	
Warranty	One year



Power Adaptor



Power Injector (POE)



Bracket



Lan cable RJ45: 1.5m



Lan Cable to device: 25m

- specifications subject to change without notice



ASU-24005G

