



2.4 GHz

WAB-24005G
Bi directional amplifier

Signal booster for your wireless AP !

802.11 **g**



Features:

- Easy Installation and mounting
- 2.4 GHz operation frequency / IEEE 802.11G compliant
- Low cost solution
- High switching speed
- High gain antenna
- Indoor Use
- DC jack built in

Output Power	26 dBm +/- 1 dBm Max
Output Range	2400-2500 MHz
Operation Mode	Bi directional TDD
Transmitting Gain	up to 12 dBm
Frequency Response	+/- 1 dBm
Signal Type	IEEE 802.11g
TX Input Power	0 dBm Min / 18 dBm Max
Receiver Gain	Up to 10 dBm
Noise Figure	3.0 dBm typical
Connectors	SMA female
LED Indicator	DC Power IN
Power Consumption	TX : <0.6A / RX: < 80mA @ 5.0 VDC
AC Adapter	AC100V-240V in / DC 5.0V 2A out
Operating Temperature	0 to +60 C



• specifications subject to change without notice

Ordering Information:

	Std Qty	Physical Dimension (LxWxH)	Weight	Accessories Include:
WAB-24005G	1 pc	3.6x2.4x1.14 inches	0.5 lb	Power adapter / Antenna / SMA cable