

## F56-x

- Standard Quantity: 100 pcs



### Information

- Brass Tin Plating
- F56-1/4" with 1/4" Ring
- Inner Diameter: 5.8 mm (0.228 in.)
- Outer Diameter: 9.1 mm (0.358 in.)
- For use with RG6 Cable

## F56CG

- Standard Quantity: 100 pcs



### Information

- Brass Tin Plating
- Connector with Annealed Ring
- Inner Diameter: 9.40 mm (0.370 in.)
- Outer Diameter: 9.48 mm (0.373 in.)
- For use with RG6 Cable

## F56CGA

- Standard Quantity: 100 pcs



### Information

- F56 Smooth Circular Crimp
- Inner Diameter: 9.40 mm (0.370 in.)
- Outer Diameter: 9.48 mm (0.373 in.)
- For use with RG6 Cable

## F56CGO

- Standard Quantity: 100 pcs



### Information

- Brass Gold Cadmium Plating
- Connector with Annealed Ring
- Inner Diameter: 9.40 mm (0.370 in.)
- Outer Diameter: 9.48 mm (0.373 in.)
- For use with RG6 Cable

## FT75-A

- Standard Quantity: 100 pcs



### Information

- 75 Ohm Terminator
- Nickel Plated Solid Brass
- Internal Plastic Seal for Exceptional Connection
- Carbon Film Resistor
- Tolerance: 2%, 1/8 W
- Return Loss: 25 dB

**F59-**

- Standard Quantity: 100 pcs

**Information**

- F59 Connector
- F59-1/4" with 1/4" Ring
- Inner Diameter: 4.55 mm (0.179 in.)
- Outer Diameter: 8.45 mm (0.333 in.)
- For use with RG59 Cable

**F59CGA**

- Standard Quantity: 100 pcs

**Information**

- Connector with Annealed Ring
- Inner Diameter: 8.65 mm (0.340 in.)
- Outer Diameter: 9.48 mm (0.373 in.)
- F59 Smooth Circular Crimp
- For use with RG59 Cable

**F59CGO**

- Standard Quantity: 100 pcs

**Information**

- Connector with Annealed Ring
- Added O-Ring for Waterproofing
- Inner Diameter: 8.65 mm (0.340 in.)
- Outer Diameter: 9.48 mm (0.373 in.)
- For use with RG59 Cable

**F59PT**

- Standard Quantity: 100 pcs

**Information**

- Female-Male Push on Adapter
- For use with RG59 Cable

**F59P**

- Standard Quantity: 100 pcs

**Information**

- Male Push on Adaptor
- For use with RG59 Cable