

WALL PLUG ADAPTERS

[CMPA-x-x] Cable Products, Hardware

Description

Taikan's wall plug adapters provide consistent power to your electronic devices. Available with a variety of output power and connector diameter options to suit your customers needs. The wall plug adapters come with a standard 1.5 meter cord.



CMPA-A-x



CMPA-B-x

Features

- Universal Input Voltage Range, 100-240 V, 50-60 Hz
- DoE and Ecodesign 2019/1782 Level VI Efficiency
- Variety of Output Power and Connector Options for Unique Applications
- Variety of Cord Lengths Available*
- Ultra-Compact Case
- Color: Black

Ordering Information

CMPA - **x** - **x**

U: US Power Adapter 110V; E: Europe Power Adapter 220V (Other regions available upon request)

A: 12 V, 2.5 Amp, 2.5 mm Connector

B: 15 V, 1.5 Amp, 1.7 mm Connector

C: 12 V, 1.0 Amp, 2.1 mm Connector

D: 12 V, 1.5 Amp, 1.5 mm Connector



CMPA-C-x

Model Number	Input	Output	Connector Diameter	Dimensions
CMPA-A-x	100 - 240 V, 50 - 60 Hz	12 V, 2.5 A	2.5 mm	5.5 x 2.5 x 10 mm
CMPA-B-x	100 - 240 V, 50 - 60 Hz	15 V, 1.5 A	1.7 mm	4.75 x 1.7 x 10 mm
CMPA-C-x	100 - 240 V, 50 - 60 Hz	12 V, 1.0 A	2.1 mm	5.5 x 2.1 x 10 mm
CMPA-D-x	100 - 240 V, 50 - 60 Hz	12 V, 1.5 A	1.5 mm	6.3 x 1.5 x 17 mm

*Cord Length Standard is set at 1.5 m but is customizable

© Copyright 2021 Taikan Company Inc. All rights reserved. This document is for information only. Features and specifications are subject to change without notice. v01262021